

XENON XP ACCESSORIES GUIDE



Honeywell

TABLE OF CONTENTS

- 1** Wall Mounts, Stands, Holders, and Covers
- 1** Charge and Communication Bases, Chargers, and Batteries
- 2** Cables and Power Supplies

WALL MOUNTS, STANDS, HOLDERS, AND COVERS



1950GSR-2-2-X
1950GHD-2-2-X
1950GSR-2USB-2-X
1950GHD-2USB-2-X

1950G Ratchet Stand

Provides a fixed stand for a corded scanner that enables presentation scanning and two-handed scanning.

50129064-001



STND-08R00-000-6



STND-15R00-000-6

STND-22F00-001-6

Rigid Presentation Stand - 3"

Stand: gray, 8 cm (3 in) height, rigid rod, large oval weighted base, cradle for Xenon™ 1900 and Xenon XP 1950 corded scanners.

Rigid Presentation Stand - 6"

Stand: gray, 15 cm (6 in) height, rigid rod, large oval weighted base, Xenon cradle.

Flexible Presentation Stand - 9"

Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon cup.



VISOR-190X-XT



VISOR 190X



UCOVERXENON



VMHOLDERE-21029

CHARGE AND COMMUNICATION BASES, CHARGERS, AND BATTERIES



BAT-SCN01A

Battery Pack

Battery: Lithium-ion battery for Xenon 1902 and Xenon XP 1952 cordless scanners.



BAT-SCN05

Smart Battery Pack

Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.



SUPCAP-SCN05

SuperCap Pack

Super Capacitor: Lithium-ion battery for Xenon XP 1952 cordless scanners.

MB4-BAT-SCN01NADO

4-Bay Battery Charger - Desk Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).

MB4-BAT-SCN01NAWO

4-Bay Battery Charger - Wall Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

CCB10-010BT-07N	CCB11-010BT-07N	CCB12-010BT-HC	CCB13-010BT-07N	CCB15-010BT-HC
1952 Presentation CCB – Black (Battery) Xenon XP 1952 Presentation CCB, black, 10 m (32.8 ft), Bluetooth®.	1952 Presentation CCB – Lyric White (Battery) Xenon XP 1952 Presentation CCB, white, 10 m (32.8 ft), Bluetooth.	1952 Presentation CCB – Healthcare (Battery) Xenon XP 1952 Presentation CCB, healthcare white, healthcare software.	1952 Desktop/Wall-Mount CCB – Black (Battery) Xenon XP 1952 Horizontal CCB, black, 10 m (32.8 ft), Bluetooth.	1952 Desktop/Wall-Mount CCB – Healthcare (Battery) Xenon XP 1952 Horizontal CCB, healthcare white, healthcare software.

CABLES AND POWER SUPPLIES

CBL-020-300-C00	CBL-120-300-C00	CBL-220-300-C00	CBL-420-300-C00	CBL-500-150-S00
RS-232 Power Cable Cable: RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8 ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle.	RS-232 Power Cable Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3 m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).	USB Power Cable USB Type A HSM 5V1.5 m (5 ft) straight cable.
CBL-500-300-S00	CBL-500-500-C00	CBL-503-300-C00	CBL-600-300-S00	CBL-600-400-C00
USB Power Cable Cable: USB, black, Type A, 3 m (9.8 ft), straight, 5V host power.	USB Power Cable Cable: USB, black, Type A, 5 m (16.4 ft), coiled, 5V host power.	USB Power Cable Cable: USB, black, 12V locking, 3 m (9.8 ft), coiled, 5V host power.	IBM Power Cable Cable: IBM 46xx Port 9b, black, 3 m (9.8 ft), straight, 12V host power.	IBM Power Cable Cable: IBM 46xx Port 9b, 12V power, coiled, 4 m (13.1 ft).
CBL-720-300-C00	CBL-MAG-300-S00	46-00525	46-00526	46-00528
Keyboard Wedge Power Cable Cable: KBW, black, PS2, 3 m (9.8 ft), coiled, 5V external power with option for host power.	RS-232 Power Cable Cable: RS-232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.	Power Supply – NA Plug Power Supply: NA plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply – EU Plug Power Supply: EU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply – AU Plug Power Supply: AU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.

46-00529

Power Supply – CN Plug

Power Supply: CN plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

Xenon XP Accessories Guide | Rev A | 06/19
© 2019 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell